

grit

MATTAS

ALWAYS A SAFE STEP AHEAD



FLEXI GRIT MATTAS



ACCESS RAMPS



ANTIFATIGUE GRIT MATTAS



GRIT MATTAS



COMFORT GRIT MATTAS

- **ANTIFATIGUE**
- **97% RECYCLED**
- **TAPERED EDGES**
- **INTERLOCKING**
- **ANTI SLIP**
- **FREE DRAINING**

SPECIFICATIONS

Dimensions: Nominal size of 500mm x 500mm x 25mm (20" x 20" x 1" high). Ramp dimensions 500mm x 100mm x 25mm high (20" x 4" x 1" at highest point).

Material: Recycled P.V.C. and Rubber with UV protection. Plasticized to a shore hardness of 67-80 shore A.

Colours: Black

Tests: Grit Mattas have a safe fall height test on concrete of 600mm (23.5 inches). Telarc registered test reports are available on request.

Load Capacity: The safe working load on the mats laid on a rigid base is 4200 kilograms (9282 lbs) per sq ft.

Temperature: Grit Mattas are suitable for use in temperatures ranging from minus 30°C (minus 22°F) to plus 90°C (184°F). Mat size increases 0-30°C (86°F): 1mm (1/32") and from 0-50°C (122°F) degrees: 2mm (1/16"). Ramp increase as for mats.

Weight: Mat weight is 2.5 kilos (5.52 lbs). Weight per box of 10=25 kgs (55.25 lbs). Ramps weight is 650 grams (1.44 lbs). Weight per box of 8 = 5.2 kgs. (12 lbs).

Packaging: Grit Mattas are packed 10 per box, carton size 605mm x 585mm x 130mm (24" x 23" x 5"). Ramps are packed 8 per box. Carton size is 510mm x 200mm x 65mm (20" x 8" x 2.5").

Shipping: A 20 ft container accommodates 6500 Grit Mattas packed in 650 cartons. The total product weight is 18,000 kgs (39,780 lbs).

For installation instructions see reverse

Silicon Carbide for Maximum Grip

